

Lovibond® Water Testing Tintometer® Group



TB 211 IR

with USB interface



- USB interface
- Range 0.01 - 1100 NTU
- Measurement according to EN ISO 7027
- Measurement with infrared light at an angle of 90 °

Part Number: 266030

The compact Lovibond® infrared turbidity measuring instruments TB 211 IR & TB 210 IR for fast and accurate on-site analysis. It is measured as provided in EN ISO 7027, the scattered light at an angle of 90 °.

The wide measuring range from 0.01 to 1100 TE / F = NTU = FNU with a detection limit of 0.01 NTU allows the use of the device in different areas, from drinking water to wastewater.

Since the measurements are made by means of infrared light, both colored and colorless water samples can be measured. A direct transfer of the measurement results to a PC is through the USB interface TB 211 IR easy to set up. The necessary USB cable is already part of the delivery.

Industry

Chemical Industry | Industries Others | Marine Industry | Municipalities | NGO | Oil and Gas | Pool Public | Pool Services

TB 211 IR

A compact instrument for reliable and easy determination of turbidity. A ring memory with 125 data sets and a USB interface guarantee an efficient data management.

Measuring Range

Test Name	Measuring Range
Turbidity	0.01 - 1100 NTU

Technical Data

Light Source	IR-LED (860 nm)
Optics	temperaturecompensated LED ($\lambda = 860$ nm) and photosensor amplifier in water proof sample chamber, infrared light
Operation	polycarbonate membrane, splash proof
Display	backlit LCD
Suitable Vials	Round Cuvettes 24 mm
Interfaces	Micro-USB
Internal Storage	internal ring memory for 125 data sets
Power Supply	9 V-block
Auto – OFF	Yes
Measuring Principle	nephelometric (90° scattered light)
Measuring Range	0,01-1100 NTU (Aurorange)
Clock	Real Time Clock and Date
Portability	Portable
Environmental Conditions	5 - 40 °C at 30 - 90 % relative humidity (non condensing)
Compliance	CE
Dimensions	110 x 55 x 190 mm
Weight	400 g (Basic unit)
Weight with Packaging	(Basic unit)

Delivery Scope Text

- Instrument in carrying case
- 4 turbidity standards (< 0,1, 20, 200 and 800 NTU)
- 9 V battery
- 2 vials (\varnothing 24 mm) with lids
- USB cable 1.5 m
- Warranty information
- Certificate of Compliance
- Instruction Manual

Accessory

Title	Part Number
Formazin Stock Solution (4000 NTU), 125 ml	194141
Formazin Stock Solution (4000 NTU), 250 ml	194142
Set turbidity standards T-CAL (<0.1, 20, 200, 800 NTU)	194150
Battery 9 V	1950012
Cleaning cloth	197635
Sample cuvettes with black lid, Height 55 mm, \varnothing 24 mm, set of 12	197655
Sample chamber lid	19801119
USB cable 1.5 m, for TB 211 IR	19802509

Australian distributor and importer:

Waterlilly Australia Pty Ltd
Tel.: +61 (0) 297989975
Email: water-lilly@bigpond.com
www.waterlillyaustralia.com

Tintometer GmbH

Lovibond® Water Testing
 Schleefstraße 8-12
 44287 Dortmund
 Tel.: +49 (0)231/94510-0
 Fax: +49 (0)231/94510-30
sales@tintometer.de
www.lovibond.com
 Germany

The Tintometer Limited

Lovibond House
 Sun Rise Way
 Amesbury, SP4 7GR
 Tel.: +44 (0)1980 664800
 Fax: +44 (0)1980 625412
water.sales@tintometer.com
www.lovibond.com
 UK

Tintometer AG

Hauptstraße 2
 5212 Hausen AG
 Tel.: +41 (0)56/4422829
 Fax: +41 (0)56/4424121
info@tintometer.ch
www.tintometer.ch
 Switzerland

Tintometer China

Room 1001, China Life Tower
 16 Chaoyangmenwai Avenue,
 Beijing, 100020
 Tel.: +86 10 85251111 App. 330
 Fax: +86 10 85251001
 China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
 Lebu Nilam 2, Bandar Bukit Tinggi,
 Klang, 41200, Selangor D.E
 Tel.: +60 (0)3 3325 2285/6
 Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
 Malaysia

Tintometer Brazil

Caixa Postal: 271
 CEP: 13201-970
 Jundiaí – SP
 Tel.: +55 (11) 3230-6410
sales@tintometer.com.br
www.lovibond.com.br
 Brazil

Tintometer Inc.

6456 Parkland Drive
 Sarasota, FL 34243
 Tel: 941.756.6410
 Fax: 941.727.9654
sales@tintometer.us
www.lovibond.com
 USA

Tintometer India Pvt. Ltd.

B-91, A.P.I.E. Sanath Nagar,
 Hyderabad, 500018
 Tel: +91 (0) 40 4647 9911
 Toll Free: 1 800 102 3891
indiaoffice@tintometer.com
www.lovibondwater.in
 India

Tintometer Spain

Postbox: 24047
 08080 Barcelona
 Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
 Spain