

# Lovibond® Water Testing Tintometer® Group



## SD30 EC



- Transparent lid for easy maintenance and storage
- Ideal lid design for a stable stand
- Display colours & symbols for easy use
- New multi-parameter models for individual measurement requirements

Part Number: 720030

### Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Municipalities | NGO | Oil and Gas | Pharmaceutical Industry | Pool Public | Pool Services

### SD30 EC

With its waterproof housing, the Pocket Tester is ideal for regular checks in industrial plants or swimming pools.

Plus, the transparent lid not only provides a secure stand for the Pocket Tester in daily use, but also makes it easier to maintain the electrodes. A three-colour LED lighting system - blue, green and red - and new display icons make the tester easy to use and intuitive to operate. The use of energy saving LEDs and 4 x AAA batteries greatly extends the life of the new Pocket Tester range to up to 2000 hours.

With the included lanyard, each SD Series tester can be worn comfortably around the neck or attached to a pocket, waistband or belt with the clip on the head of the tester, allowing it to be taken anywhere without tiring the hands.

### Measuring Range

Test Name	Measuring Range
Conductivity	0.01 - 20.00 mS/cm
Salinity	0.01 - 10 g/L
TDS	0.01 - 20.00 ppt

### Technical Data

<b>Accuracy</b>	Con/TDS/Salt: $\pm 1\%$ FS Temperature: $\pm 0.5\text{ }^{\circ}\text{C}$
<b>Display</b>	3 coloured backlit LCD (blue: measurement, green: calibration, red: alarm)
<b>Auto – OFF</b>	Yes
<b>Calibration</b>	1 or 2 points calibration for auto mode Standard: 1413 $\mu\text{S/cm}$ or Standard: 12.88 mS/cm up to 2 points calibration for manual mode $\pm 50\%$ adjustable value
<b>Power Supply</b>	4 micro batteries (AAA)
<b>Battery Life Time</b>	> 2000 hours
<b>Portability</b>	Portable
<b>Temperature Compensation</b>	Automatic
<b>Resolution</b>	Auto Scale - Con 0.1 $\mu\text{S/cm}$ , 1 $\mu\text{S/cm}$ , 0.01 mS/cm; Auto Scale – TDS: 0.1 ppm, 1 ppm, 0.01 ppt; Salt: 0.01 ppt
<b>Resolution Temperature</b>	0.1 $^{\circ}\text{C}$
<b>Calibration Points</b>	1- 3
<b>Buffer Auto Recognition</b>	Con: 84 $\mu\text{S/cm}$ / 1413 $\mu\text{S/cm}$ / 12 mS/cm
<b>Calibration Indicator</b>	Yes
<b>Stability Indicator</b>	Yes
<b>Auto-Hold Function</b>	Yes
<b>Alarm Limits</b>	Yes
<b>Environmental Conditions</b>	0 - 60 $^{\circ}\text{C}$ / 0 - 80% rel. humidity (non-condensing)
<b>Protection Class</b>	IP 67

<b>Compliance</b>	CE
<b>Dimensions</b>	40 x 40 x 180 mm
<b>Weight</b>	151 g
<b>Weight with Packaging</b>	268 g

## Delivery Scope

- Tester incl. electrode
- 4 AAA batteries
- Lanyard
- Storage box
- Multilingual instruction manual
- Certificate of compliance
- Warranty declaration

## Accessories

Title	Part Number
Micro batteries (AAA), set of 4	1950026
Conductivity (1413 µS) and TDS (998 ppm) calibration solution	467642
Conductivity (12.89 mS) and TDS (9.02 ppth) calibration solution	467643
Replacement electrode for SD30 EC	720035

### Australian distributor and importer:

Waterlilly Australia Pty Ltd  
 Tel.: +61 (0) 297989975  
[water-lilly@bigpond.com](mailto:water-lilly@bigpond.com)  
[www.waterlillyaustralia.com](http://www.waterlillyaustralia.com)  
 Australia

### Tintometer GmbH

Lovibond® Water Testing  
 Schleefstraße 8-12  
 44287 Dortmund  
 Tel.: +49 (0)231/94510-0  
[sales@lovibond.com](mailto:sales@lovibond.com)  
[www.lovibond.com](http://www.lovibond.com)  
 Germany

### The Tintometer Limited

Lovibond House  
 Sun Rise Way  
 Amesbury, SP4 7GR  
 Tel.: +44 (0)1980 664800  
 Fax: +44 (0)1980 625412  
[sales@lovibond.uk](mailto:sales@lovibond.uk)  
[www.lovibond.com](http://www.lovibond.com)  
 UK

### Tintometer China

9F, SOHO II C.  
 No.9 Guanghualu,  
 Chaoyang District,  
 Beijing, 100020  
 Customer Care China Tel.: 4009021628  
 Tel.: +86 10 85251111 Ext. 330  
 Fax: +86 10 85251001  
[chinaoffice@tintometer.com](mailto:chinaoffice@tintometer.com)  
[www.lovibond.com](http://www.lovibond.com)  
 China

### Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,  
 Lebu Nilam 2, Bandar Bukit Tinggi,  
 Klang, 41200, Selangor D.E  
 Tel.: +60 (0)3 3325 2285/6  
 Fax: +60 (0)3 3325 2287  
[lovibond.asia@tintometer.com](mailto:lovibond.asia@tintometer.com)  
[www.lovibond.com](http://www.lovibond.com)  
 Malaysia

### Tintometer Brazil

Caixa Postal: 271  
 CEP: 13201-970  
 Jundiaí – SP  
 Tel.: +55 (11) 3230-6410  
[sales@lovibond.us](mailto:sales@lovibond.us)  
[www.lovibond.com.br](http://www.lovibond.com.br)  
 Brazil

### Tintometer Inc.

6456 Parkland Drive  
 Sarasota, FL 34243  
 Tel: 941.756.6410  
 Fax: 941.727.9654  
[sales@lovibond.us](mailto:sales@lovibond.us)  
[www.lovibond.us](http://www.lovibond.us)  
 USA

### Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
 Sanathnagar Industrial Estate,  
 Hyderabad, 500018  
 Telangana  
 Tel: +91 (0) 40 23883300  
 Toll Free: 1 800 599 3891/ 3892  
[indiaoffice@lovibond.in](mailto:indiaoffice@lovibond.in)  
[www.lovibondwater.in](http://www.lovibondwater.in)  
 India

### Tintometer Spain

Postbox: 24047  
 08080 Barcelona  
 Tel.: +34 661 606 770  
[sales@tintometer.es](mailto:sales@tintometer.es)  
[www.lovibond.com](http://www.lovibond.com)  
 Spain

### Australian distributor and importer:

Waterlilly Australia Pty Ltd  
 Tel.: +61 (0) 297989975  
 Email: [water-lilly@bigpond.com](mailto:water-lilly@bigpond.com)  
[www.waterlillyaustralia.com](http://www.waterlillyaustralia.com)